# Product datasheet

Specifications



## Circuit breaker, ComPacT NSX250F, 36kA/415VAC, 4 poles 3D (neutral not protected), TMD trip unit 200A

C25F6TM200

## Main

| | |
|---|---|
| **Range** | ComPacT |
| **Product name** | ComPacT NSX |
| **Device short name** | NSX250F |
| **Product or component type** | Circuit breaker |
| **Device application** | Distribution |
| **Poles description** | 4P |
| **Protected poles description** | 3D |
| **Neutral position** | Left |
| **[In] rated current** | 200 A at 40 °C |
| **[Ue] rated operational voltage** | 690 V AC 50/60 Hz |
| **Network type** | AC |
| **Network frequency** | 50/60 Hz |
| **Suitability for isolation** | Yes conforming to EN/IEC 60947-2 |
| **Utilisation category** | Category A |
| **Breaking capacity** | 85 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>36 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>35 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>30 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>22 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>8 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2<br>85 kA Icu at 240 V AC 50/60 Hz conforming to UL 60947-4-1<br>35 kA Icu at 480 V AC 50/60 Hz conforming to UL 60947-4-1<br>15 kA Icu at 600 V AC 50/60 Hz conforming to UL 60947-4-1 |
| **Breaking capacity code** | F 36 kA 415 V AC |
| **Trip unit name** | TM-D |
| **Trip unit technology** | Thermal-magnetic |
| **Trip unit protection functions** | LI |
| **control type** | Toggle |
| **Circuit breaker mounting mode** | Fixed |

## Complementary

| | |
|---|---|
| **[Ui] rated insulation voltage** | 800 V AC 50/60 Hz |
| **[Uimp] rated impulse withstand voltage** | 8 kV |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **[Ics] rated service breaking capacity** | 85 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>36 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>35 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>30 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>22 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>8 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| **Mechanical durability** | 20000 cycles |
| **Electrical durability** | 20000 cycles at 440 V In/2<br>10000 cycles at 440 V In<br>10000 cycles at 690 V In/2<br>5000 cycles at 690 V In |
| **Power dissipation per pole** | 15.4 W |
| **Mounting support** | Backplate |
| **Mounting position** | Horizontal and vertical<br>Flat on the back |
| **Upside connection** | Front |
| **Downside connection** | Front |
| **Connection pitch** | 35 mm |
| **Protection type** | L : for overload protection (thermal)<br>I : for short-circuit protection (magnetic) |
| **Trip unit rating** | 200 A at 40 °C |
| **Long-time pick-up adjustment type Ir (thermal protection)** | Adjustable |
| **[Ir] long-time protection pick-up adjustment range** | 0.7...1 x In |
| **Long-time protection delay adjustment type tr** | Fixed |
| **[tr] long-time delay adjustment range** | 120…400 s at 1.5 x In<br>15 s at 6 x Ir |
| **Neutral protection setting** | No protection (3D) |
| **Instantaneous protection pick-up adjustment type Ii** | Adjustable |
| **[Ii] instantaneous protection pick-up adjustment range** | 5...10 x In |
| **Earth-leakage protection** | Without |
| **Number of slots** | 5 slot(s) |
| **Width (W)** | 140 mm |
| **Height (H)** | 161 mm |
| **Depth (D)** | 86 mm |
| **Net weight** | 2.8 kg |

# Environment

| | |
|---|---|
| **Standards** | EN/IEC 60947-2 |
| **Overvoltage category** | III |
| **Electrical shock protection class** | Class II on front face |
| **Pollution degree** | 3 conforming to IEC 60664-1 |
| **IP degree of protection** | IP40 conforming to IEC 60529 |
| **IK degree of protection** | IK07 conforming to IEC 62262 |
| **Ambient air temperature for operation** | -25…70 °C |
| **Ambient air temperature for storage** | -50…85 °C |

| | |
|---|---|
| **Relative humidity** | 0…95 % |
| **Operating altitude** | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 14.000 cm |
| **Package 1 Width** | 14.900 cm |
| **Package 1 Length** | 19.300 cm |
| **Package 1 Weight** | 2.630 kg |
| **Unit Type of Package 2** | S03 |
| **Number of Units in Package 2** | 3 |
| **Package 2 Height** | 30.000 cm |
| **Package 2 Width** | 30.000 cm |
| **Package 2 Length** | 40.000 cm |
| **Package 2 Weight** | 8.340 kg |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | 272 |
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant with Exemptions |
| SCIP Number | 3874e08b-fcb8-4aa9-87c4-d36abebf2833 |
| REACh Regulation | REACh Declaration |
| Halogen-free status | Product contains halogen above thresholds |
| PVC free | Yes |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| End of life manual availability | End of Life Information |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Offer Marketing Illustration

**Product benefits / Features**



Offer Marketing Illustration

**Product benefits / Features**



Offer Marketing Illustration

**Product benefits / Features**



Offer Marketing Illustration

**Product benefits / Features**



Technical Illustration

**Assembly's dimensions**

