Product data sheet

Specifications



Circuit breaker, ComPact NSX160F, 36kA/415VAC, TMD trip unit 125A, 3 poles 3d

LV430631

Discontinued on: Jun 15, 2023

Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility
Important message: This product has been switched to new ComPacT range and is no longer commercialized.

Main

Range	ComPact
Product name	ComPact NSX
Range of Product	ComPact NSX100...250
Device short name	NSX160F
Product or Component Type	Circuit breaker
Device Application	Distribution
Number of poles	3P
Protected poles description	3t
Line Rated Current	125 A 104 °F (40 °C)
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network Frequency	50/60 Hz
Suitability for isolation	Yes EN/IEC 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	10 kA 600 V AC 50/60 Hz UL 508 85 kA 240 V AC 50/60 Hz UL 508 22 kA Icu 525 V AC 50/60 Hz IEC 60947-2 35 kA Icu 440 V AC 50/60 Hz IEC 60947-2 36 kA Icu 380/415 V AC 50/60 Hz IEC 60947-2 8 kA Icu 660/690 V AC 50/60 Hz IEC 60947-2 85 kA Icu 220/240 V AC 50/60 Hz IEC 60947-2 35 kA 480 V AC 50/60 Hz UL 508 30 kA Icu 500 V AC 50/60 Hz IEC 60947-2
Performance level	F 36 kA 415 V AC
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
Control Type	Toggle
Circuit breaker mounting mode	Fixed

Complementary

[Ui] rated insulation voltage	800 V AC 50/60 Hz

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[Uimp] rated impulse withstand voltage	8 kV
[Ics] rated service short-circuit breaking capacity	35 kA 440 V AC 50/60 Hz IEC 60947-2 36 kA 380/415 V AC 50/60 Hz IEC 60947-2 85 kA 220/240 V AC 50/60 Hz IEC 60947-2 22 kA 525 V AC 50/60 Hz IEC 60947-2 30 kA 500 V AC 50/60 Hz IEC 60947-2 8 kA 660/690 V AC 50/60 Hz IEC 60947-2
Mechanical durability	40000 cycles
Electrical durability	7500 cycles 690 V In 15000 cycles 690 V In/2 20000 cycles 440 V In 40000 cycles 440 V In/2
Mounting Support	Backplate
Upside connection	Front
Downside connection	Front
Connection pitch	1.4 in (35 mm)
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rating	125 A 104 °F (40 °C)
Long-time pick-up adjustment type Ir (thermal protection)	Adjustable
[Ir] long-time protection pick-up adjustment range	0.7...1 x In
Long-time protection delay adjustment type tr	Fixed
[tr] long-time protection delay adjustment range	120…400 s 1.5 x In 15 s 6 x Ir
Short-time protection pick-up adjustment type Isd	Fixed
[Isd] Short-time protection pick-up adjustment range	1250 A
Short-time protection delay adjustment type tsd	Fixed
Earth-leakage protection	Without
Number of slots for electrical auxiliaries	5
Width (W)	4.1 in (105 mm)
Height (H)	6.3 in (161 mm)
Depth (D)	3.4 in (86 mm)
Net Weight	4.9 lb(US) (2.2 kg)

Environment

Standards	EN/IEC 60947
Product Certifications	CCC EAC Marine
Overvoltage category	Class II
Electrical shock protection class	Class II
Pollution degree	3 IEC 60664-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Ambient Air Temperature for Operation	-13…158 °F (-25…70 °C)

Ambient Air Temperature for Storage	-58…185 °F (-50…85 °C)
Relative humidity	0…95 %
Operating altitude	0...6561.68 ft (0...2000 m) without derating 2000 m...5000 m with derating

Ordering and shipping details

Category	US10DE201101
Discount Schedule	0DE2
GTIN	3606480011344
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.4 in (13.8 cm)
Package 1 Width	4.5 in (11.5 cm)
Package 1 Length	7.6 in (19.2 cm)
Package weight(Lbs)	4.006 lb(US) (1.817 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	12
Package 2 Height	11.8 in (30 cm)
Package 2 Width	15.7 in (40 cm)
Package 2 Length	23.6 in (60 cm)
Package 2 Weight	49.89 lb(US) (22.63 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	443

Use Better

Materials and Substances

EU RoHS Directive	Compliant with Exemptions
SCIP Number	3874e08b-fcb8-4aa9-87c4-d36abebf2833
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.