# Product datasheet

Specifications



## circuit breaker Masterpact NW10H1 - 1000 A - 3 poles - drawout - w/o trip unit

48245

## Main

| | |
|---|---|
| **Range** | MasterPacT |
| **Product name** | MasterPact NW |
| **Circuit breaker name** | MasterPact NW10H1 |
| **Product or component type** | Circuit breaker |
| **Device application** | Power distribution protection |
| **Poles description** | 3P |
| **Control unit** | Without control unit |
| **[In] rated current** | 1000 A at 40 °C |
| **Performance type** | H1 65 kA 440 V AC |
| **[Ue] rated operational voltage** | 690 V AC 50/60 Hz |
| **Suitability for isolation** | Yes conforming to EN/IEC 60947-2 |
| **Selectivity category** | Category B |
| **Control type** | Push-button |
| **Mounting mode** | Drawout |

## Complementary

| | |
|---|---|
| **[Icu] rated ultimate short-circuit breaking capacity** | 65 kA at 220/415 V AC 50/60 Hz<br>65 kA at 440 V AC 50/60 Hz<br>65 kA at 525 V AC 50/60 Hz<br>65 kA at 690 V AC 50/60 Hz |
| **[Ics] rated service breaking capacity** | 65 kA at 220/415 V AC 50/60 Hz<br>65 kA at 440 V AC 50/60 Hz<br>65 kA at 525 V AC 50/60 Hz<br>65 kA at 690 V AC 50/60 Hz |
| **[Icw] rated short-time withstand current** | 65 kA 1 s<br>36 kA 3 s |
| **[Icm] rated short-circuit making capacity** | 143 kA 220/415 V AC at 50/60 Hz<br>143 kA 440 V AC at 50/60 Hz<br>143 kA 525 V AC at 50/60 Hz<br>143 kA 690 V AC at 50/60 Hz |
| **Sensor rating** | 400 A<br>1000 A |
| **[Ui] rated insulation voltage** | 1000 V AC 50/60 Hz |
| **[Uimp] rated impulse withstand voltage** | 12 kV |
| **Power dissipation in W** | 150 W |
| **Maximum breaking time** | 25 ms |
| **Maximum closing response time** | 70 ms |

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Mounting support** | Backplate<br>Rails |
| **Upside connection** | Front<br>Rear |
| **Downside connection** | Front<br>Rear |
| **Connection pitch** | 115 mm |
| **Mechanical durability** | 12500 cycles without maintenance<br>25000 cycles with maintenance |
| **Electrical durability** | 10000 cycles 440 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2<br>10000 cycles 690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2<br>AC-23A: 10000 cycles 440 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3<br>AC-23A: 10000 cycles 690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3<br>AC-3: 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3 |
| **Height** | 439 mm |
| **Width** | 441 mm |
| **Depth** | 395 mm |
| **Net weight** | 90 kg |
| **Standards** | EN/IEC 60947-1<br>EN/IEC 60947-2 |
| **Product certifications** | CE<br>CCC<br>EAC |

## Environment

| | |
|---|---|
| **IP degree of protection** | IP30 conforming to IEC 60529 |
| **Pollution degree** | 4 conforming to IEC 60664-1 |
| **Ambient air temperature for operation** | -25…70 °C |
| **Ambient air temperature for storage** | -40…85 °C |
| **Operating altitude** | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 30.5 cm |
| **Package 1 Width** | 29.5 cm |
| **Package 1 Length** | 37.5 cm |
| **Package 1 Weight** | 47.036 kg |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **1 440 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **434 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **11 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **15 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **824 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **156 kg CO2 eq.** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **Yes** |
| Packaging without single use plastic | **No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards** |
| EU RoHS Directive | **Compliant with Exemptions** |
| SCIP Number | **6a3c1e0b-44cb-4a11-80eb-a083722777c1** |
| REACh Regulation | **REACh Declaration** |
| Halogen-free status | **Product contains halogen above thresholds** |
| PVC free | **Yes** |
| Silicone-free | **No** |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | **No** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **69** |
| End of life manual availability | **End of Life Information** |
| Take-back | **No** |
| WEEE Label | **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins** |