
Product data sheet

Specifications



Circuit breaker frame, MasterPact MTZ2 25H1 fixed for MicroLogic X, 2500A, 66kA/415VAC (Icu), 3P

LV848070

Main

Range	MasterPacT
Product name	MasterPact MTZ2
Device short name	MTZ2 25 H1
Product or Component Type	Circuit breaker
Device Application	Power distribution protection
Poles description	3P
Control type	Without control unit
Product compatibility	control unit MicroLogic 2.0 X control unit MicroLogic 5.0 X control unit MicroLogic 6.0 X control unit MicroLogic 7.0 X control unit MicroLogic 2.0 Xi control unit MicroLogic 5.0 Xi control unit MicroLogic 6.0 Xi control unit MicroLogic 7.0 Xi
Line Rated Current	2500 A 104 °F (40 °C)
Breaking capacity code	H1 66 kA 415 V AC
[Ue] rated operational voltage	690 V AC 50/60 Hz
Suitability for isolation	Yes EN/IEC 60947-2
Selectivity category	Category B
Control Type	Push-button
Mounting Mode	Fixed

Complementary

Breaking capacity	66 kA 220/415 V AC 50/60 Hz 66 kA 440 V AC 50/60 Hz 66 kA 500/525 V AC 50/60 Hz 66 kA 660/690 V AC 50/60 Hz
[Ics] rated service breaking capacity	66 kA 220/415 V AC 50/60 Hz 66 kA 440 V AC 50/60 Hz 66 kA 500/525 V AC 50/60 Hz 66 kA 660/690 V AC 50/60 Hz
[Icw] rated short-time withstand current	66 kA 0.5 s 66 kA 1 s 66 kA 3 s
[Icm] rated short-circuit making capacity	145 kA 220/415 V AC 50/60 Hz 145 kA 440 V AC 50/60 Hz 145 kA 500/525 V AC 50/60 Hz 145 kA 660/690 V AC 50/60 Hz

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sensor rating	1250 A 1600 A 2000 A 2500 A
[Ui] rated insulation voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	12 kV
Power dissipation in W	260 W
Maximum breaking time	25 ms
Maximum closing response time	70 ms
Mounting Support	Rails Base plate
Upside connection	Front Rear
Downside connection	Front Rear
Connection pitch	4.5 in (115 mm)
Mechanical durability	20000 cycles with periodic preventive maintenance
Electrical durability	AC-3 6000 cycles 440/690 V AC 50/60 Hz EN/IEC 60947-3 2500 cycles 690 V AC 50/60 Hz EN/IEC 60947-2 5000 cycles 440 V AC 50/60 Hz EN/IEC 60947-2 AC-23A 2500 cycles 690 V AC 50/60 Hz EN/IEC 60947-3 AC-23A 5000 cycles 440 V AC 50/60 Hz EN/IEC 60947-3
Height	13.9 in (352 mm)
Width	16.6 in (422 mm)
Depth	11.8 in (300 mm)
Net Weight	110.2 lb(US) (50 kg)
Standards	EN/IEC 60947-1 EN/IEC 60947-2 EN/IEC 60947-2 Annex H IEC 61557-12
Product Certifications	CE IECEE CB Scheme

Environment

IP degree of protection	IP30 conforming to EN 60529
Pollution degree	3 IEC 60947-1
Ambient Air Temperature for Operation	-13…158 °F (-25…70 °C)
Ambient Air Temperature for Storage	-40…185 °F (-40…85 °C)
Operating altitude	0...6561.68 ft (0...2000 m) without derating 2000...5000 m with derating

Ordering and shipping details

GTIN	3606480808425

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	11.6 in (29.5 cm)

Package 1 Width	12.008 in (30.5 cm)
Package 1 Length	14.8 in (37.5 cm)
Package weight(Lbs)	104.171 lb(US) (47.251 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**1 861 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**314 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**7 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**8 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**1 429 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**103 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards**
SCIP Number	**F31d8a4d-e9cb-4afc-bf2c-5965742ce772**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
Halogen content performance	**Product contains halogen above thresholds**
PVC free	**Yes**
Silicon free	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**71**
Circularity Profile	End of Life Information
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**