Product datasheet

Specifications



Circuit breaker frame, MasterPact MTZ2 32H2 fixed for MicroLogic X, 3200A, 100kA/415VAC (Icu), 4P right neutral

LV848181

Main

Range	MasterPacT
Product name	MasterPact MTZ2
Device short name	MTZ2 32 H2
Product or component type	Circuit breaker
Device application	Power distribution protection
Poles description	4P
Neutral position	Right
Control type	Without control unit
Product compatibility	control unit MicroLogic 2.0 X control unit MicroLogic 5.0 X control unit MicroLogic 6.0 X control unit MicroLogic 7.0 X control unit MicroLogic 2.0 Xi control unit MicroLogic 5.0 Xi control unit MicroLogic 6.0 Xi control unit MicroLogic 7.0 Xi
[In] rated current	3200 A at 40 °C
Breaking capacity code	H2 100 kA 415 V AC
[Ue] rated operational voltage	690 V AC 50/60 Hz
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Selectivity category	Category B
Control type	Push-button
Mounting mode	Fixed

Complementary

Breaking capacity	100 kA at 220/415 V AC 50/60 Hz 100 kA at 440 V AC 50/60 Hz 85 kA at 500/525 V AC 50/60 Hz 85 kA at 660/690 V AC 50/60 Hz
[Ics] rated service breaking capacity	100 kA at 220/415 V AC 50/60 Hz 100 kA at 440 V AC 50/60 Hz 85 kA at 500/525 V AC 50/60 Hz 85 kA at 660/690 V AC 50/60 Hz
[Icw] rated short-time withstand current	85 kA 0.5 s 85 kA 1 s 75 kA 3 s
[Icm] rated short-circuit making capacity	220 kA 220/415 V AC at 50/60 Hz 220 kA 440 V AC at 50/60 Hz 187 kA 500/525 V AC at 50/60 Hz 187 kA 660/690 V AC at 50/60 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Integrated instantaneous protection (DIN in kA peak)	171…209 kA
Sensor rating	1600 A 2000 A 2500 A 3200 A
[Ui] rated insulation voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	12 kV
Power dissipation in W	420 W
Maximum breaking time	25 ms
Maximum closing response time	70 ms
Mounting support	Rails Base plate
Upside connection	Front Rear
Downside connection	Front Rear
Connection pitch	115 mm
Mechanical durability	20000 cycles with periodic preventive maintenance
Electrical durability	AC-3: 6000 cycles 440/690 V AC 50/60 Hz conforming to EN/IEC 60947-3 2500 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-2 5000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 AC-23A: 2500 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-3 AC-23A: 5000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3
Height	352 mm
Width	537 mm
Depth	300 mm
Net weight	65 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-2 EN/IEC 60947-2 Annex H IEC 61557-12
Product certifications	CE IECEE CB Scheme

Environment

IP degree of protection	IP30 conforming to EN 60529
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-40…85 °C
Operating altitude	0...2000 m without derating 2000...5000 m with derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.0 cm
Package 1 Width	30.0 cm
Package 1 Length	50.0 cm

Package 1 Weight	36.252 kg

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**2 830 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**388 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**8 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**10 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**2 297 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**127 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Packaging

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards**
SCIP Number	**F31d8a4d-e9cb-4afc-bf2c-5965742ce772**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	**Product contains halogen above thresholds**
PVC free	**Yes**
Silicone-free	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**71**
End of life manual availability	End of Life Information
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**