Product datasheet

Specifications



Circuit breaker Masterpact MTZ2 40H2, 4000 A, 3P drawout, without Micrologic

LV848323

Main

Range	MasterPacT
Product name	MasterPact MTZ2
Device short name	MTZ2 40 H2
Product or component type	Circuit breaker
Device application	Power distribution protection
Poles description	3P
Control type	Without control unit
Product compatibility	control unit MicroLogic 2.0 X control unit MicroLogic 5.0 X control unit MicroLogic 6.0 X control unit MicroLogic 7.0 X control unit MicroLogic 2.0 Xi control unit MicroLogic 5.0 Xi control unit MicroLogic 6.0 Xi control unit MicroLogic 7.0 Xi
[In] rated current	4000 A at 40 °C
Breaking capacity code	H2 100 kA 415 V AC
[Ue] rated operational voltage	690 V AC 50/60 Hz
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Selectivity category	Category B
Control type	Push-button
Mounting mode	Drawout

Complementary

Breaking capacity	100 kA at 220/415 V AC 50/60 Hz 100 kA at 440 V AC 50/60 Hz 85 kA at 500/525 V AC 50/60 Hz 85 kA at 660/690 V AC 50/60 Hz
[Ics] rated service breaking capacity	100 kA at 220/415 V AC 50/60 Hz 100 kA at 440 V AC 50/60 Hz 85 kA at 500/525 V AC 50/60 Hz 85 kA at 660/690 V AC 50/60 Hz
[Icw] rated short-time withstand current	85 kA 0.5 s 85 kA 1 s 75 kA 3 s
[Icm] rated short-circuit making capacity	220 kA 220/415 V AC at 50/60 Hz 220 kA 440 V AC at 50/60 Hz 187 kA 500/525 V AC at 50/60 Hz 187 kA 660/690 V AC at 50/60 Hz
Integrated instantaneous protection (DIN in kA peak)	171…209 kA

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sensor rating	2000 A 2500 A 3200 A 4000 A
[Ui] rated insulation voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	12 kV
Power dissipation in W	900 W
Maximum breaking time	25 ms
Maximum closing response time	70 ms
Mounting support	Rails Base plate
Upside connection	Front Rear
Downside connection	Front Rear
Connection pitch	150 mm
Mechanical durability	20000 cycles with periodic preventive maintenance
Electrical durability	AC-3: 6000 cycles 440/690 V AC 50/60 Hz conforming to EN/IEC 60947-3 2500 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-2 5000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 AC-23A: 2500 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-3 AC-23A: 5000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3
Height	Drawout circuit breaker with chassis: 439 mm Drawout circuit breaker without chassis: 300 mm
Width	Drawout circuit breaker with chassis: 441 mm Drawout circuit breaker without chassis: 378 mm
Depth	Drawout circuit breaker with chassis: 403 mm Drawout circuit breaker without chassis: 300 mm
Net weight	90 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-2 EN/IEC 60947-2 Annex H IEC 61557-12
Product certifications	CE IECEE CB Scheme

Environment

IP degree of protection	IP30 conforming to EN 60529
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-40…85 °C
Operating altitude	0...2000 m without derating 2000...5000 m with derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	29.5 cm
Package 1 Length	37.5 cm

Package 1 Weight	51.895 kg

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**5 684 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**571 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**12 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**14 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**4 899 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**187 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards**
SCIP Number	**F31d8a4d-e9cb-4afc-bf2c-5965742ce772**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	**Product contains halogen above thresholds**
PVC free	**Yes**
Silicone-free	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**71**
End of life manual availability	End of Life Information
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**